

FESTFLOOR

TECHNICAL DATA SHEET

3K PLUS

Additive that improves the properties of the PU FEST 2K sealer



DESCRIPTION

3K PLUS is an additive that improves the mechanical properties and scratch resistance of the PU FEST 2K polyurethane sealer.

TECHNICAL DATA

- Dosage: 10% relative to component A of PU FEST 2K
- Color: colorless
- Open time: 45 minutes
- Shelf life: 12 months
- Application temperature: +15°C ÷ +25°C
- Light foot traffic possible after 24h, full load after 7 days.

DIRECTIONS FOR USE

When mixing the components of PU FEST 2K in a 5:1 ratio (5 parts by weight of component A; 1 part by weight of component B), add 3K PLUS in an amount of 10% relative to component A, and then add 10% water relative to all components. For example: 5 kg of component A + 1 kg of component B (mix) + 0.5 kg of 3K PLUS (mix) + 10% water (0.65 kg). Then mix everything thoroughly for about 2-3 minutes. It is not recommended to add more 3K PLUS than the recommended amount.

PACKAGING

- 100 g,
- 0.5 kg.

SAFETY AND HEALTH

Causes eye irritation. May cause drowsiness or dizziness. Frequent contact may cause drying and cracking of the skin. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Wear protective gloves / protective clothing / eye protection / face protection. If you feel unwell, contact a doctor. Dispose of waste at special collection points.