

FESTFLOOR

TECHNICAL DATA SHEET

FESTGRUNT

Product for surface strengthening of absorbent substrates before application of microcement



DESCRIPTION

Acrylic priming agent for surface priming, evens out absorbency and improves adhesion. Ideal before applying microcement, paints, decorative plasters, screeds, etc.

PROPERTIES

- seals the substrate
- prevents water from being drawn out of the mortar
- increases the adhesion of the mortar to the substrate
- improves the flow of self-levelling mortars
- vapour-permeable

TECHNICAL DATA

- Consumption: 0.1-0.3 kg/m² - depending on the absorbency of the surface
- Color: milky
- Density: 1.0 g/cm³
- pH: 8
- Application temperature: +15°C ÷ +25°C
- Drying time: after 2-4 hours
- Shelf life: 12 months in the original unopened packaging. Protect from frost.

DIRECTIONS FOR USE

The surface must be perfectly hardened, dry, clean and free from oils, greases, paint residues and other loose materials. Shake the FEST Grunt container well before use. Apply with a roller or brush. On uneven or very absorbent surfaces, it is recommended to apply the product in several coats. Leave to dry for 2-4 hours. After this time, further work can be started.

PACKAGING

- 1 kg
- 5 kg

CLEANING OF TOOLS

Clean equipment and tools with water immediately after use.

SAFETY AND HEALTH

The product is intended for professionals. Before starting work, read the Safety Data Sheets for the components included in the system, available on request from the manufacturer. May cause skin irritation. May cause eye damage. May cause an allergic skin reaction. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs, seek medical advice/attention. Dispose of contents/container in accordance with local regulations. Keep out of reach of children.