

FESTFLOOR

TECHNICAL DATA SHEET

FESTKontakt

Quartz bonding bridge under plasters and fillers, for smooth, non-absorbent surfaces of walls and ceilings, concrete, OSB boards, drywall boards and ceramic tiles, etc.



DESCRIPTION

FEST Kontakt is a ready-to-use bonding compound based on high-quality dispersion resins and mineral fillers. It provides excellent adhesion to many types of substrate and creates a durable bond between successive layers of the surface finish.

WHERE TO USE?

- For exterior and interior use
- For smooth surfaces
- For ceramic tiles
- Bonding layer between the existing substrate and successive layers of the surface finish
- For walls and ceilings
- Under microcement and decorative plasters

PROPERTIES

- Very high adhesion to all types of substrates
- Ready to use
- Single-layer thickness <2 mm
- Resistant to low and high temperatures
- Resistant to UV radiation
- High abrasion resistance
- Contains no solvents
- Fast drying time

PACKAGING

- 5 kg
- 10 kg
- 15 kg
- 20 kg

CLEANING OF TOOLS

Clean equipment and tools with water immediately after use.
Remove hardened material mechanically.

TECHNICAL DATA

- Density: approximately 1.8 kg/dm³
- Adhesion to substrate: >1.0 MPa
- Consumption: 1 layer - 0.7-1.0 kg/m²; 2 layers - 1.5-2.0 kg/m²
- Application temperature: +15°C to +25°C

APPLICATION

The substrate must be: strong, load-bearing, dry (substrate moisture must not exceed 4%), clean, stable, and free of dust and oil. During application, the temperature of the bonding bridge, the substrate and the surroundings should not be lower than 15°C. Before use, mix the FESTKontakt bonding bridge thoroughly; do not dilute. Apply evenly to the substrate using a trowel. When reinforcing the substrate, the Fibermesh should be embedded immediately after spreading FESTKontakt on the floor. Drying time depends on the temperature and humidity in the room as well as the absorbency of the substrate. Under conditions of 20°C, the next layers can be applied after 4-6 hours.

SAFETY AND HEALTH

The product is intended for professionals. Before starting work, read the technical data sheets of the components included in the system, available at www.festfloor.com. Avoid contact with skin, mucous membranes, eyes, etc. In the event of accidental contact, wash with soap and water and seek medical advice. Take measures to prevent dusting or splashing with the mortar. Keep out of the reach of children. It is recommended to use masks and gloves. In enclosed rooms, ensure good ventilation and avoid inhaling dust.