

FESTFLOOR

TECHNICAL DATA SHEET

FF ANTI-SLIP

Water-based anti-slip agent, recommended for hard surfaces.



DESCRIPTION

FF ANTI-SLIP (PRO AGENT) is a concentrated, water-based anti-slip solution that does not require rinsing, is non-aggressive, and leaves no visible changes on the surface. It is used to prevent and reduce the risk of falls. It can be used on most hard surfaces (varnished parquet, ceramic, stoneware, marble, resin, microcement, PVC, LVT, etc.) Moreover, thanks to its formula, it does not stain and leaves no marks.

TECHNICAL DATA

- Yield: 1 L - 70 m²
- Storage stability: 12 months in original sealed containers at temperatures from +10°C to +25°C.

DIRECTIONS FOR USE

Before use, shake well. Clean the surface thoroughly with a non-invasive detergent (e.g. FEST Cleaner) and leave to dry. Dilute FF ANTI-SLIP and then proceed with application. Pour in 3 capfuls (150 ml) per 1 liter of water. Recommended frequency of use: repeat the treatment as needed and at regular intervals. WARNING: Keep out of reach of children. If medical advice is needed, have product container or label at hand.

PACKAGING

- 1 L

SAFETY AND HEALTH

WARNING: May cause an allergic skin reaction. Dispose of waste at designated collection points. Keep out of reach of children. Wear protective gloves. If medical advice is needed, have product container or label at hand. Avoid breathing dust / fume / gas / mist / vapours / spray. Contains: ROSIN.