

FESTFLOOR

TECHNICAL DATA SHEET

FF Wax Care

Wax for maintaining microcement floors, for indoor use.



DESCRIPTION

FF WAX CARE is a water-resistant wax for the care of lacquered, oiled and/or waxed wooden floors, microcement and stone. Its special formula renews and protects matte, scratched or damaged floors.

PROPERTIES

- protects and maintains the sealer
- creates a hydrophobic coating
- increases abrasion resistance
- does not affect the appearance of the sealer

TECHNICAL DATA

- Yield: approx. 70-90 m²/L
- Color: colorless
- Application temperature: +10°C ÷ +25°C
- Drying time: 30 minutes*
- Full curing: 12-24 h*
- * At 20°C and 65% relative humidity.
- Shelf life: 24 months in original unopened packaging. Store at temperatures from +10°C to +25°C. Protect from frost and direct sunlight.

DIRECTIONS FOR USE

Shake well before use. Apply FF WAX CARE by spraying it onto the surface to be refreshed. Spread the product evenly with a cloth. Make sure not to leave excess product on the surface. After 30 minutes, once completely dry, polish the surface with a soft cloth or a white pad. Carry out regular maintenance by applying another layer of FEST WAX. The use of rough and hard cloths for applying the wax is not recommended. Note: Using FF WAX CARE on low-absorbency surfaces may increase slipperiness, especially in the presence of water or high humidity. Before use, it is recommended to test on a small area. Long-term exposure to temperatures below +10°C may cause the product to thicken. Store at a temperature above +15°C before use.

PACKAGING

- 500 ml

SAFETY AND HEALTH

Protect from frost during transport and storage. Avoid prolonged exposure to temperatures below +10°C. Keep out of reach of children. If medical advice is needed, have the product container or label at hand. EUH066 Repeated exposure may cause skin dryness or cracking. EUH210 Safety data sheet available on request. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P271 Use only outdoors or in a well-ventilated area.