

FESTFLOOR

TECHNICAL DATA SHEET

FF Wax

Wax for maintaining microcement floors, for indoor use.



DESCRIPTION

FF Wax is a wax- and acrylic-based product that, once applied, forms a waterproof protective and maintenance coating. This coating is hard, abrasion-resistant and has anti-slip properties. The product is intended for varnished surfaces, including microcement floors. It works very well as an additional protective coating. It can also be successfully used as a sealer restorer. Odourless, vapour-permeable, resistant to polishing and alcohol-based disinfection.

TECHNICAL DATA

- Efficiency: product consumption depends on the surface and application method and averages approx. 1-3 l per 100 m² per coat
- Color: milky
- pH: 8,0-9,0
- Shelf life: 24 months in the original, unopened packaging. Store the product at a temperature above 15°C, protect from frost and direct sunlight.
- Application temperature: +15°C ÷ +25°C
- Appearance: satin or high Gloss

DIRECTIONS FOR USE

The surface must be dry before application of the product (moisture below 3%) and thoroughly vacuumed and washed. Shake the FF Wax container well. The product is ready to use and must not be diluted. Apply in sections, using a microfiber mop, in 2-3 thin coats. The drying time between coats is at least 60 minutes. Additional polishing to increase Gloss can be carried out with a soft pad after the surface has fully dried (2-3 days). Do not use outdoors – the product is sensitive to low temperatures.

PACKAGING

- 1 L

SAFETY AND HEALTH

Observe the general occupational health and safety rules and any other rules contained in the product safety data sheet, available on request. The product is a non-hazardous substance, does not present a transport hazard, has not been classified into any toxicity class, and does not require special precautions for storage. The product is a mixture of the highest-quality ingredients, mainly: waxes, acrylics, preservatives, solvent, surfactants.