

# FESTFLOOR

## TECHNICAL DATA SHEET

### FF FIX PRO

#### Floor maintenance product



## DESCRIPTION

FF FIX PRO is a polyurethane resin-based product intended for the maintenance of heavily worn floors exposed to high traffic, including wooden, resin, microcement and resilient floors such as LVT, PVC or linoleum.

## TECHNICAL DATA

- Coverage: 1 L - 40-60 m<sup>2</sup>
- Storage stability: 12 months in originally sealed containers at a temperature from +10°C to +25°C.

## DIRECTIONS FOR USE

Shake thoroughly before use. Make sure the surface is dry, degreased and free of wax and dust. Then clean the surface with FEST Cleaner according to the instructions. Once the surface has been cleaned, you can proceed with the application of FF FIX PRO. Lightly wipe the floor with a cloth dampened with water, pour a small amount of FF FIX PRO and begin application, ensuring even distribution of the product, without leaving an excessive amount of the product on the working surface.

NOTES: The floor can be put back into use after 2-3h. Avoid moving furniture and rugs for 12-24h after application. The next cleaning can be carried out after three days using suitable detergents. It is recommended to perform a preliminary test to check adhesion to the substrate.

## PACKAGING

The product is supplied in a 1L package.

## SAFETY AND HEALTH

WARNING: Keep out of the reach of children. If medical advice is needed, have the product container or label at hand.