

FESTFLOOR

TECHNICAL DATA SHEET

NANO SILVER PLUS SB

Special silver-ion additive for solvent-based sealers



DESCRIPTION

NANO SILVER PLUS SB is a special silver-ion additive for PU FEST TURBO solvent-based sealer. It creates a hygienic protective coating. It does not change the hardness of the sealer. It does not affect gloss or viscosity. It preserves the mechanical and chemical resistance of the sealer. Certified according to ISO 22196.

TECHNICAL DATA

- Color: colorless
- Application temperature: +15°C ÷ +25°C
- Light foot traffic is possible after 24 hours, full load after 7 days
- Open time: 1 hour
- Shelf life: 12 months in original unopened packaging, at temperatures from +10°C to +25°C

DIRECTIONS FOR USE

Shake thoroughly before use. Add NANO SILVER PLUS SB to PU FEST TURBO at a ratio of 2% to the total of the components and sealer. Mix thoroughly. Apply with a microfiber roller, as with the other sealers from the Festfloor line. It is not recommended to add more NANO SILVER PLUS SB than recommended.

- For PU FEST TURBO sealer (5kg + 2,5kg), add 150 g of NANO SILVER PLUS SB.
- For PU FEST TURBO sealer (0,8kg + 0,4kg), add 25 g of NANO SILVER PLUS SB.

PACKAGING

- 150 g.
- 25 g.

SAFETY AND HEALTH

H332 Harmful if inhaled. H372 Causes damage to organs through prolonged or repeated exposure. H318 Causes serious eye damage. H317 May cause an allergic skin reaction. H410 Very toxic to aquatic life with long lasting effects. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P280 Wear protective gloves/protective clothing/eye protection/face protection. P310 Immediately call a POISON CENTER or doctor. P273 Avoid release to the environment. P391 Collect spillage. Contains: 3-iodo-2-propynylbutylcarbamate